FORMAT: USA MATERIAL SAFETY DATA SHEET

PRODUCT: GE5040 RTV SILICONE RUBBER COMPOUND

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED BY: SUPPLIED BY:

GE SILICONES GE SILICONES

260 HUDSON RIVER ROAD 260 HUDSON RIVER ROAD

WATERFORD, NY 12188 WATERFORD, NY 12188

EMERGENCY PHONE (24 HRS) EMERGENCY PHONE (24 HRS)

(518) 237-3330 (518) 237-3330

REVISED: 01/29/03

PREPARER: JH MERRIFIELD

CHEMICAL FAMILY/USE: SILICONE RUBBER SEALANT

FORMULA: MIXTURE

2. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION/ APPROX. ACGIH TLV OSHA PEL

CAS REG NO. WGT. % TWA STEL TWA STEL UNITS

HAZARDOUS

METHYLTRIMETHOXYSILANE

1185-55-3 1-5 200(R) NE 200(R) NE PPM

HEXAMETHYLDISILAZANE

999-97-3 1-5 25(R) NE 35STEL NE (R) PPM

DISTILLATES, PETROLEUM, HYDROTREATED

LIGHT

64742-47-8 5-10 NE NA NE NA NA

2. NON-HAZARDOUS

ME-DIMETHOXY/STPD POLYDIME-SILOXANE

68037-58-1 60-80 NE NE NE NE NA

DIMETHYLPOLYSILOXANE

63148-62-9 10-30 NE NA NE NA NA

TETRAMER TREATED FUMED SILICA

68583-49-3 10-30 10 NE 15 NE MG/M3

See Section 15 for description of any WHMIS Trade Secret(s).

3. HAZARDS IDENTIFICATION

1 EMERGENCY OVERVIEW:

WARNING!

May cause skin, eye, and stomach irritation.

Harmful if swallowed, inhaled, or absorbed through skin.

May cause central nervous system depression.

Refer to other MSDS sections for detailed information.

Ammonia odor

Translucent solid

POTENTIAL HEALTH EFFECTS:

INGESTION:

May cause stomach discomfort.

May be harmful if swallowed.

May cause central nervous system effects.

May cause gastrointestinal irritation, nausea, vomiting, and $\operatorname{diarrhea}$.

Not an expected route of exposure.

SKIN CONTACT:

Uncured product contact will irritate lips, gums and tongue.

Uncured product contact may irritate the skin.

May cause mild skin irritation.

May be absorbed through skin and produce effects as listed

```
May cause mild eye irritation.
MEDICAL CONDITIONS AGGRAVATED:
Pre-existing skin or respiratory diseases.
SUBCHRONIC (TARGET ORGAN) EFFECTS:
Central nervous system
Skin
CHRONIC EFFECTS/CARCINOGENICITY:
This product or one of its ingredients present 0.1% or more
is NOT listed as a carcinogen or suspected carcinogen by
NTP, IARC, or OSHA.
PRODUCTS/INGREDIENTS
This space reserved for special use.
PRINCIPLE ROUTES OF EXPOSURE:
Oral.
Dermal - skin.
Eyes.
Inhalation.
OTHER:
This product contains methylpolysiloxanes which can generate
formaldehyde at approximately 300 degrees Fahrenheit (150'C)
and above, in atmospheres which contain oxygen. Formaldehyde
is a skin and respiratory sensitizer, eye and throat irritant,
acute toxicant, and potential cancer hazard. An MSDS for
formaldehyde is available from GE Silicones.
4. FIRST AID MEASURES
```

page: 3

under "Ingestion".

Causes mild respiratory irritation.

Applies only in uncured state.

Uncured product contact irritates eyes.

COPYRIGHT GENERAL ELECTRIC CO.

May also cause other effects as listed under "Ingestion".

INHALATION:

EYE CONTACT:

INGESTION:

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

SKIN:

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water.

Get medical attention if irritation persists.

INHALATION:

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN:

None known.

5. FIRE FIGHTING MEASURES

FLASH POINT: NA (C) NA (F)

METHOD : NA

IGNITION TEMP : UNK (C) UNK (F)

FLAMMABLE LIMITS IN AIR - LOWER (%): NA
FLAMMABLE LIMITS IN AIR - UPPER (%): NA
SENSITIVITY TO MECHANICAL IMPACT (Y/N): NO

SENSITIVITY TO STATIC DISCHARGE:

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA:

 ${\tt All \ standard \ firefighting \ media}$

SPECIAL FIREFIGHTING PROCEDURES:

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6 ACCIDENTAL RELEASE MEASURES

1

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Wipe, scrape or soak up in an inert material and put in a container for disposal.

Wash walking surfaces with detergent and water to reduce slipping hazard.

Wear proper protective equipment as specified in the protective equipment section.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container closed when not in use.

Avoid contact with skin and eyes.

Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation.

Use mechanical ventilation to stay below TLV of 25 ppm ammonia.

Store away from heat, sources of ignition, and incompatibles.

Product releases methanol during application and curing.

COPYRIGHT GENERAL ELECTRIC CO.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION
ENGINEERING CONTROLS:
Showers.
Eyewash stations.
See "Ventilation" below.
RESPIRATORY PROTECTION:
If exposure limits are exceeded or respiratory irritation is
experienced, NIOSH/MSHA approved respiratory protection should
be worn. Supplied air respirators may be required for
non-routine or emergency situations. Respiratory protection
must be provided in accordance with OSHA regulations (see 29
CFR 1910.134).
PROTECTIVE GLOVES:
Cloth gloves.
EYE AND FACE PROTECTION:
Safety glasses.
OTHER PROTECTIVE EQUIPMENT:
Wear eye protection and protective clothing.
VENTILATION:
Ventilation and other forms of engineering controls are
preferred for controlling exposures. Respiratory protection
may be needed for non-routine or emergency situations.
9. PHYSICAL AND CHEMICAL PROPERTIES

Keep away from children.

PRODUCT INFORMATION:

BOILING POINT : NA (C) NA (F)

VAPOR PRESSURE(20 C)(MM HG): NA
VAPOR DENSITY (AIR=1): NA

FREEZING POINT : NA (C) NA (F)
MELTING POINT : UNK (C) UNK (F)

PHYSICAL STATE : SOLID
ODOR : AMMONIA

COLOR : TRANSLUCENT

ODOR THRESHOLD (PPM) UNK % VOLATILE BY VOLUME : NA EVAP. RATE(BUTYL ACETATE=1): <1 SPECIFIC GRAVITY (WATER=1) : 1.05 DENSITY (KG/M3) UNK ACID/ALKALINITY (MEQ/G) : NA PΗ NA VOC EXCL.H2O & EXEMPTS(G/L): 27

SOLUBILITY IN WATER (20 C) : INSOLUBLE

SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT): PARTIALLY IN TOLUENE

10. STABILITY AND REACTIVITY

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS THERMAL DECOMPOSITION/COMBUSTION PRODUCTS:

Carbon monoxide.

Carbon dioxide.

Silicon dioxide.

Methanol.

Ammonia.

Formaldehyde.

INCOMPATIBILITY (MATERIALS TO AVOID):

COPYRIGHT GENERAL ELECTRIC CO.

page: 7

None known.
CONDITIONS TO AVOID:
None known.
11. TOXICOLOGICAL INFORMATION
1
PRODUCT INFORMATION:
ACUTE ORAL LD50 (MG/KG): UNKNOWN
ACUTE DERMAL LD50 (MG/KG): UNKNOWN
ACUTE INHALATION LC50 (MG/L): UNKNOWN
OTHER:
None.
AMES TEST: UNKNOWN
12. ECOLOGICAL INFORMATION
ECOTOXICOLOGICAL INFORMATION: No data at this time
CHEMICAL FATE INFORMATION: No data at this time
13. DISPOSAL CONSIDERATIONS
DISPOSAL METHOD:

COPYRIGHT GENERAL ELECTRIC CO.

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT SHIPPING NAME: NONE

DOT HAZARD CLASS: NOT DOT REGULATED

DOT LABEL(S): NONE
UN/NA NUMBER: NONE
PLACARDS: NONE

IATA:

NOT REGULATED BY IATA

IMO IMDG-code: NOT REGULATED FOR OCEAN TRANSPORTATION

EMS No: NA
EUROPEAN CLASS:

RID (OCTI): NONE
ADR (ECE): NONE
RAR (IATA): NONE

15. REGULATORY INFORMATION

SARA SECTION 302:

None Found

1 SARA (311,312) HAZARD CLASS:

ACUTE HEALTH HAZARD

NONE

SARA (313) CHEMICALS:

NONE

CPSC CLASSIFICATION: NA

COPYRIGHT GENERAL ELECTRIC CO.

page: 9

NONE
WHMIS HAZARD CLASS:
D2A VERY TOXIC MATERIALS
D2B TOXIC MATERIALS
WHMIS TRADE SECRET:
None
EXPORT:
SCHDLE B/HTSUS: 3214.10 Mastic Based on Rubber
3206.49 Silicone Color Concentrate
ECCN: EAR99
EAR99
HAZARD RATING SYSTEMS
HMIS FLAMMABILITY 0 , REACTIVITY 0 , HEALTH 1
FLAMMABILITY 0 , REACTIVITY 0 , HEALTH 0
NFPA HEALTH = 1, FLAMMABILIITY = 0 , REACTIVITY = 0
CALIFORNIA PROPOSITION 65:
NONE
16. OTHER INFORMATION
This product or its components are on the European inventory of
existing commercial chemicals (EINECS)
These data are offered in good faith as typical values and not
as product specifications. No warranty, either expressed or
implied, is made. The recommended industrial hygiene and safe
handling procedures are believed to be generally applicable.
However, each user should review these recommendations in the
specific context of the intended use and determine whether they
are appropriate.

This product or its components are on the Australian inventory

COPYRIGHT GENERAL ELECTRIC CO.

..... C = ceiling limit NEGL = negligible EST= estimated NF = none found NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recomm. By vendor By-product = reaction by- SKN = skin product, TSCA inventory TS = trade secret status not required under R = recommended 40 CFR part 720.30(h-2) MST = mist ${\tt STEL}$ = short term exposure ${\tt NT}$ = not tested limit

(ACOIN).....

*